

LA-CO Industries, Inc.

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Date of issue: 18/06/2015

Revision date: 06/01/2016

Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses


Main use category : Professional use
Use of the substance/mixture : Temperature indicator

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

LA-CO Industries Europe S.A.S.
Parc Industriel de la Plaine de l'Ain - Allée des Combes.
01150.BLYES.France.
Phone: +33 (0)4 74 46 23 23
Fax: +33 (0)4 74 46 23 29
E-mail: info@eu.laco.com
Web: http://www.markal.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
AUSTRIA	Vergiftungsinformationszentrale (Poisons Information Centre)	Allgemeines Krankenhaus Waehringer Geurtel 18-20 1090 Wien	+43 1 406 43 43
BELARUS	The Belarus Republican Poisons Centre	Kizhevatova str. 58 220115 Minsk	+375 (0)17 201 9158
BELGIUM	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245
BULGARIA	Национален токсикологичен информационен център National Clinical Toxicology Centre, Emergency Medical Institute "Pirogov"	21 Toltleben Boulevard 1606 SOFIA	+359 2 9154 409

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

CROATIA	Poisons Control Centre Institute of Medical Research & Occupational Health	Ksaverska Cesta 2 P.O. Box 291 HR-10000 Zagreb	+385 1 234 8342
CZECH REPUBLIC	Toxikologické informační středisko Clinic For Occupational Medicine, 1st Medical Faculty, Charles University	Na Bojišti 1 120 00 Praha 2	+42 2 2491 9293 +42 2 2491 5402
DENMARK	Gifflinjen Bispebjerg Hospital	Bispebjerg Bakke 23, 60, 1 DK-2400 København NV	+45 82 12 12 12 +45 35 31 55 55
ESTONIA	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	+372 626 93 90
FINLAND	Myrkytystietokeskus	P.O.B 340 (Haartmaninkatu 4) HUS SF - 00029 Helsinki	+358 9 471 977
FRANCE	ORFILA		+33 1 45 42 59 59
GERMANY	Berliner Betrieb für Zentrale Gesundheitliche Aufgaben	Oranienburger Strasse 285 13437 Berlin	+49 30 19240
GERMANY	Informations und Beratungszentrum für Vergiftungsfälle	Kirrberger Straße, Gebäude 9 D-66421 Homburg/Saar	+49 6841 19240
GERMANY	Beratungstelle bei Vergiftungen, Klinische Toxikologie und Beratungsstelle bei Vergiftungen	Langenbeckstrasse 1 55131 Mainz	+49 6131 19240
GREECE	Poisons Information Centre	11527 Athens	+30 10 779 3777
HUNGARY	Országos Kémiai Biztonsági Intézet (National Institute of Chemical Safety) Egészségügyi Toxikológiai Tájékoztató Szolgálat (Health Toxicological Information Service)	1437 Budapest PO Box 839 1097 Budapest, Nagyvárad tér 2	+36 80 20 11 99
ICELAND	Eitrunarmiðstöðin	Eitrunarmiðstöðin 108 Reykjavik	+354 543 22 22
IRELAND	National Poisons Information Centre	Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166
LATVIA	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs	2 Hipocrate Street LV 1038 Rīga	+371 67 04 24 73
LITHUANIA	Apsinuodijimų kontrolės ir informacijos biuras	Siltnamiu 29 2043 Vilnius	+370 5 236 20 52/+370 687 53 378
MALTA	Medicines & Poisons Info Office	Mater Dei Hospital, Msida MSD 2090 Malta	25450000
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88
PORTUGAL	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica (INEM)	Rua Almirante Barroso, 36 1000-013 Lisboa	808 250 143 (for use only in Portugal), +351 21 330 3284
ROMANIA	Biroul pentru Regulamentul Sanitar International si Informare Toxicologica	Str. Dr. Leonte Anastasievici Nr.1-3, Sector 5 50463 Bucuresti	+40 21 318 36 06
SLOVAKIA	Národné toxikologické informačné centrum University Hospital Bratislava	Limbová 5 833 05 Bratislava	+421 2 54 77 4 166
SPAIN	Servicio de Información Toxicológica Instituto Nacional de Toxicología, Departamento de Madrid	Calle Luis Cabrera 9 E-28002 Madrid	+34 91 562 04 20
SWEDEN	Giflinformationscentralen Swedish Poisons Information Centre, Karolinska Hospital	Box 60 500 SE-171 76 Stockholm	+46 8 33 12 31 (International) 112 (National)

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

SWITZERLAND	Centre Suisse d'Information Toxicologique	Freiestrasse 16 Postfach CH-8028 Zurich	+41 44 251 51 51 (International) 145 (National)
-------------	---	---	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request

2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
sebacic acid	(CAS No) 111-20-6 (EC no) 203-845-5	0 – 95	Not classified
potassium sulfate	(CAS No) 7778-80-5 (EC no) 231-915-5	0 – 95	Not classified
succinimide	(CAS No) 123-56-8 (EC no) 204-635-6	0 – 95	Not classified
barium sulfate	(CAS No) 7727-43-7 (EC no) 231-784-4	0 – 90	Not classified
2',4'-dimethylacetoacetanilide	(CAS No) 97-36-9 (EC no) 202-576-0	0 – 85	Acute Tox. 4 (Oral), H302
calcium sulfate	(CAS No) 7778-18-9 (EC no) 231-900-3	0 – 55	Not classified
adipic acid	(CAS No) 124-04-9 (EC no) 204-673-3 (EC index no) 607-144-00-9	0 – 20	Eye Irrit. 2, H319
salicylamide	(CAS No) 65-45-2 (EC no) 200-609-3	0 – 9	Acute Tox. 4 (Oral), H302
Iron oxide red	(CAS No) 1309-37-1 (EC no) 215-168-2	0 – 2	Aquatic Chronic 2, H411
butyl 4-hydroxybenzoate	(CAS No) 94-26-8 (EC no) 202-318-7	0 – 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
phenyl salicylate	(CAS No) 118-55-8 (EC no) 204-259-2	0 – 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
lithium sulphate	(CAS No) 10377-48-7 (EC no) 233-820-4	0 – 2	Acute Tox. 4 (Oral), H302

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polyethylene Glycol	(CAS No) 25322-68-3 (EC no) 500-038-2	0 – 3	Not classified
manganese dioxide	(CAS No) 1313-13-9 (EC no) 215-202-6 (EC index no) 025-001-00-3	0 – 0.5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332
Aluminum oxide	(CAS No) 1344-28-1 (EC no) 215-691-6	0 – 0.5	Not classified
Silicon dioxide (cristobalite)	(CAS No) 14808-60-7 (EC no) 238-878-4	< 0.1	Carc. 1A, H350i
Carbon black	(CAS No) 1333-86-4 (EC no) 215-609-9	< 0.1	Carc. 2, H351

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Wash with plenty of soap and water.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
- First-aid measures after ingestion : Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand. Water spray.
- Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No specific fire or explosion hazard. Burning produces irritating, toxic and noxious fumes.
- Hazardous decomposition products in case of fire : Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing. EN469.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid creating or spreading dust.

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable gloves.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable gloves.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Avoid generating dust. Contain and collect as any solid.
Methods for cleaning up : Minimize generation of dust. On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.
Incompatible products : Strong oxidizers. Strong bases.
Prohibitions on mixed storage : Keep away from incompatible materials.
Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Temperature indicator.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

barium sulfate (7727-43-7)		
Belgium	Remark (BE)	(sulfate de)
Slovakia	NPHV (priemerná) (mg/m ³)	1.5 mg/m ³ (respirabilná frakcia) 4 mg/m ³ (inhalovateľná frakcia)
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ inhalable aerosol 4 mg/m ³ respirable aerosol
Iron oxide red (1309-37-1)		
Belgium	Remark (BE)	(trioxyde de; fumées, en Fe)
Denmark	Grænseværdie (kortvarig) (mg/m ³)	7 mg/m ³
Denmark	Anmærkninger (DK)	(Jernoxid, total dust)
Finland	Huomautus (FI)	(Fe)
Hungary	Megjegyzések (HU)	(respirabilis por)
Ireland	OEL (8 hours ref) (mg/m ³)	5 mg/m ³ (Iron oxide, fume as Fe) 10 mg/m ³ (Rouge total inhalable dust) 4 mg/m ³ (Rouge total respirable dust)

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Iron oxide red (1309-37-1)		
Ireland	OEL (15 min ref) (mg/m ³)	10 mg/m ³ (Iron oxide, fume as Fe)
Lithuania	Remark (LT)	(biūrėk IX skyriaus 3 pastabà.)
Poland	Remark (PL)	(dymy)
Slovakia	NPHV (priemerná) (mg/m ³)	1.5 mg/m ³ (respirabilná frakcia) 4 mg/m ³ (inhalovateľná frakcia)
Spain	Notes	(Óxido de hierro(III) (polvo y humos), como Fe)
Sweden	Anmärkning (SE)	(Järnoxid, respirabelt damm)
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ (Rouge, inhalable fraction) 4 mg/m ³ (Rouge, respirable fraction) 5 mg/m ³ (fume, as Fe)
United Kingdom	WEL STEL (mg/m ³)	10 mg/m ³ (fume, as Fe)
Norway	Merknader (NO)	(Jern(III)oksid, beregnet som Fe)
Switzerland	Remark (CH)	(alveolengängiger Staub)
Aluminum oxide (1344-28-1)		
Austria	MAK (mg/m ³)	10 mg/m ³ (gemessen als einatembarer Aerosolanteil) 5 mg/m ³ (alveolengängiger Anteil)
Austria	MAK Short time value (mg/m ³)	20 mg/m ³ (gemessen als einatembarer Aerosolanteil) max. 2x60 min./Schicht 10 mg/m ³ (alveolengängiger Anteil) max. 2x60 min./Schicht
Belgium	Limit value (mg/m ³)	10 mg/m ³
Belgium	Remark (BE)	(oxyde d') (en Al)
Denmark	Grænseværdie (langvarig) (mg/m ³)	5 mg/m ³ (total) 2 mg/m ³ (respirabel)
Denmark	Grænseværdie (kortvarig) (mg/m ³)	10 mg/m ³ (total) 4 mg/m ³ (respirabel)
France	VME (mg/m ³)	10 mg/m ³
France	Note (FR)	(respirable aerosol)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	3 mg/m ³
Germany	Remark (TRGS 900)	(gemessen als alveolengängiger Staubanteil)
Hungary	AK-érték	6 mg/m ³
Hungary	Megjegyzések (HU)	(respirable aerosol)
Ireland	OEL (8 hours ref) (mg/m ³)	10 mg/m ³ (total inhalable dust) 4 mg/m ³ (respirable dust)
Lithuania	IPRV (mg/m ³)	2 mg/m ³
Lithuania	Remark (LT)	(alveolinė frakcija. biūrėk IX skyriaus 3 pastabà.)
Poland	NDS (mg/m ³)	2.5 mg/m ³ (dymy, pyl calkowity) 1.2 mg/m ³ (dymy, pyl respirabilny)
Slovakia	NPHV (priemerná) (mg/m ³)	1.5 mg/m ³ (respirabilná frakcia) 4 mg/m ³ (inhalovateľná frakcia)
Spain	VLA-ED (mg/m ³)	10 mg/m ³
Sweden	nivågränsvärde (NVG) (mg/m ³)	5 mg/m ³ (inhalable aerosol) 2 mg/m ³ (respirable aerosol)

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Aluminum oxide (1344-28-1)		
United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ (inhalable aerosol) 4 mg/m ³ (respirable aerosol)
Norway	Grenseverdier (AN) (mg/m ³)	10 mg/m ³
Norway	Merknader (NO)	1)
Switzerland	VME (mg/m ³)	3 mg/m ³
Switzerland	Remark (CH)	(respirable aerosol)
manganese dioxide (1313-13-9)		
Finland	HTP-arvo (8h) (mg/m ³)	0.2 mg/m ³
Silicon dioxide (cristobalite) (14808-60-7)		
Austria	MAK (mg/m ³)	0.15 mg/m ³
Austria	Remark (AT)	(alveolengängige Fraktion; Jahres-Miw)
Belgium	Limit value (mg/m ³)	0.1 mg/m ³
Belgium	Remark (BE)	(poussières alvéolaires)
Denmark	Grænseværdie (langvarig) (mg/m ³)	0.3 mg/m ³ (inhalable aerosol) 0.1 mg/m ³ (K, respirable aerosol)
Denmark	Grænseværdie (kortvarig) (mg/m ³)	0.6 mg/m ³ (inhalable aerosol) 0.2 mg/m ³ (K, respirable aerosol)
Finland	HTP-arvo (8h) (mg/m ³)	0.05 mg/m ³
Finland	Huomautus (FI)	(alveolijae)
France	VME (mg/m ³)	0.1 mg/m ³
France	Note (FR)	(poussières alvéolaires de quartz)
Hungary	AK-érték	0.15 mg/m ³
Hungary	Megjegyzések (HU)	(respirable aerosol)
Ireland	OEL (8 hours ref) (mg/m ³)	0.1 mg/m ³
Lithuania	IPRV (mg/m ³)	0.1 mg/m ³
Lithuania	Remark (LT)	(piūrėk IX skyriaus 3 pastabà)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	0.075 mg/m ³
Netherlands	Remark (MAC)	(Voor respirabel stof) (kankerverwekkende stof)
Poland	NDS (mg/m ³)	2 mg/m ³ (krzemionke powyzej 50%; pyl calkowity) 0.3 mg/m ³ (krzemionke powyzej 50%; pyl respirabilny) 2 mg/m ³ (krzemionke od 2% do 50%; pyl calkowity) 0.3 mg/m ³ (krzemionke od 2% do 50%; pyl respirabilny)
Slovakia	NPHV (priemerná) (mg/m ³)	0.1 mg/m ³
Slovakia	Upozornenie (SK)	(Dokázaný karcinogén pre ľudí, R)
Spain	VLA-ED (mg/m ³)	0.1 mg/m ³
Spain	Notes	(respirable aerosol)
Sweden	nivågränsvärde (NVG) (mg/m ³)	0.1 mg/m ³
Sweden	Anmärkning (SE)	(respirabelt damm; M, 1)
Switzerland	VME (mg/m ³)	0.15 mg/m ³
Switzerland	Remark (CH)	(respirable aerosol)

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

sebacic acid (111-20-6)		
Lithuania	IPRV (mg/m ³)	4 mg/m ³
Carbon black (1333-86-4)		
Belgium	Limit value (mg/m ³)	3.5 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	3.5 mg/m ³
Denmark	Anmærkninger (DK)	K
Finland	HTP-arvo (8h) (mg/m ³)	3.5 mg/m ³
Finland	HTP-arvo (15 min)	7 mg/m ³
France	VME (mg/m ³)	3.5 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	3.5 mg/m ³
Ireland	OEL (15 min ref) (mg/m ³)	7 mg/m ³
Spain	VLA-ED (mg/m ³)	3.5 mg/m ³
Sweden	nivågränsvärde (NVG) (mg/m ³)	3 mg/m ³
United Kingdom	Local name	Carbon black
United Kingdom	WEL TWA (mg/m ³)	3.5 mg/m ³
United Kingdom	WEL STEL (mg/m ³)	7 mg/m ³
Norway	Grenseverdier (AN) (mg/m ³)	3.5 mg/m ³
adipic acid (124-04-9)		
Finland	HTP-arvo (8h) (mg/m ³)	5 mg/m ³
Poland	Remark (PL)	pyly
Spain	VLA-ED (mg/m ³)	5 mg/m ³
Polyethylene Glycol (25322-68-3)		
Austria	MAK (mg/m ³)	1000 mg/m ³ (einatembare Fraktion)
Austria	MAK Short time value (mg/m ³)	4000 mg/m ³ max. 4x15 min./Schicht (einatembare Fraktion)
Denmark	Grænseværdie (langvarig) (mg/m ³)	1000 mg/m ³
Denmark	Grænseværdie (kortvarig) (mg/m ³)	2000 mg/m ³
Denmark	Anmærkninger (DK)	(Polyethylenglycol (PEG) med middelmolvægt på 200-600)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	1000 mg/m ³
Germany	TRGS 900 Limitation of exposure peaks (mg/m ³)	8000 mg/m ³
Germany	Remark (TRGS 900)	(einatembare Fraktion)
Slovakia	NPHV (priemerná) (mg/m ³)	1000 mg/m ³
Slovakia	Upozornenie (SK)	krátkodobý: kategória II.
Switzerland	VME (ppm)	1000 ppm
Switzerland	Remark (CH)	(mittlere Molmasse 200–600)
potassium sulfate (7778-80-5)		
Lithuania	IPRV (mg/m ³)	10 mg/m ³
calcium sulfate (7778-18-9)		
Belgium	Remark (BE)	(sulfate de)
Hungary	Megjegyzések (HU)	(respirable aerosol)

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

calcium sulfate (7778-18-9)		
Slovakia	NPHV (priemerná) (mg/m ³)	1.5 mg/m ³ (respirabilná frakcia) 4 mg/m ³ (inhalovateľná frakcia)
United Kingdom	WEL TWA (mg/m ³)	4 mg/m ³ (respirable dust) 10 mg/m ³ (inhalable dust)
Switzerland	VME (mg/m ³)	3 mg/m ³
Switzerland	Remark (CH)	(respirable aerosol)

8.2. Exposure controls

Appropriate engineering controls	: Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear dust impervious gloves. EN374.
Eye protection	: EN166. In case of dust production: protective goggles.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges. EN 12083.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Keep away from incompatible materials. Avoid dust formation.

10.5. Incompatible materials

Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Not classified.

barium sulfate (7727-43-7)	
LD50 oral rat	307 g/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	307000.000 mg/kg bodyweight
phenyl salicylate (118-55-8)	
LD50 oral rat	3000 mg/kg
ATE CLP (oral)	3000.000 mg/kg bodyweight
butyl 4-hydroxybenzoate (94-26-8)	
LD50 oral rat	13200 mg/kg
ATE CLP (oral)	13200.000 mg/kg bodyweight
2',4'-dimethylacetoacetanilide (97-36-9)	
LD50 oral rat	1995 mg/kg
ATE CLP (oral)	1995.000 mg/kg bodyweight
salicylamide (65-45-2)	
LD50 oral rat	1400 mg/kg
ATE CLP (oral)	1400.000 mg/kg bodyweight
Iron oxide red (1309-37-1)	
LD50 oral rat	> 10000 mg/kg
Aluminum oxide (1344-28-1)	
LD50 oral rat	> 15900 mg/kg
LC50 inhalation rat (mg/l)	7.6 mg/l/4h
ATE CLP (vapours)	7.600 mg/l/4h

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

Aluminum oxide (1344-28-1)	
ATE CLP (dust,mist)	7.600 mg/l/4h
manganese dioxide (1313-13-9)	
ATE CLP (oral)	500.000 mg/kg bodyweight
ATE CLP (dust,mist)	1.500 mg/l/4h
sebacic acid (111-20-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
succinimide (123-56-8)	
LD50 oral rat	14000 mg/kg 24 h
ATE CLP (oral)	14000.000 mg/kg bodyweight
Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m ³ 4 h
adipic acid (124-04-9)	
LD50 oral rat	5560 mg/kg
LD50 dermal rabbit	7940 ml/kg
LC50 inhalation rat (mg/l)	> 7.7 mg/l/4h
ATE CLP (oral)	5560.000 mg/kg bodyweight
Polyethylene Glycol (25322-68-3)	
LD50 oral rat	47000 mg/kg
LD50 dermal rat	> 20000 mg/kg
ATE CLP (oral)	47000.000 mg/kg bodyweight
potassium sulfate (7778-80-5)	
LD50 oral rat	> 2000 mg/kg OECD 425
LD50 dermal rat	> 2000 mg/kg OECD Test Guideline 402
LC50 inhalation rat (mg/l)	> 1.2 mg/l/4h OECD Guideline 433
lithium sulphate (10377-48-7)	
LD50 oral rat	613 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 2 mg/l/4h
ATE CLP (oral)	613.000 mg/kg bodyweight
calcium sulfate (7778-18-9)	
LD50 oral rat	> 1581 mg/kg No mortality observed
LC50 inhalation rat (mg/l)	> 3.26 mg/l/4h No mortality observed
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
barium sulfate (7727-43-7)	
NOAEL (chronic, oral, animal/male, 2 years)	60 mg/kg bodyweight
NOAEL (chronic, oral, animal/female, 2 years)	75 mg/kg bodyweight

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

lithium sulphate (10377-48-7)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight

calcium sulfate (7778-18-9)	
NOAEL (chronic, oral, animal/male, 2 years)	8400 mg/kg bodyweight

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

potassium sulfate (7778-80-5)	
NOAEL (oral, rat)	>= 1500 mg/kg bodyweight Animal testing did not show any effects on fertility, mutagenic, or teratogenic effects.

Specific target organ toxicity (repeated exposure) : Not classified

adipic acid (124-04-9)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight/day

potassium sulfate (7778-80-5)	
NOAEL (oral, rat, 90 days)	256 mg/kg bodyweight/day

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

barium sulfate (7727-43-7)	
LC50 fish 1	> 3.5 mg/l 96 h
EC50 Daphnia 1	14500 µg/l 48 h

2,4'-dimethylacetoacetanilide (97-36-9)	
LC50 fish 1	250 (250 - 350) mg/l

salicylamide (65-45-2)	
LC50 fish 1	101 mg/l 96 h
EC50 Daphnia 1	75 mg/l 24 h

Iron oxide red (1309-37-1)	
EC50 Daphnia 1	> 100 mg/l

Aluminum oxide (1344-28-1)	
EC50 Daphnia 1	> 1470 mg/l
NOEC (acute)	> 50 mg/l

manganese dioxide (1313-13-9)	
LC50 fish 1	> 100 % v/v saturated solution, 96 h
EC50 Daphnia 1	> 100 % v/v saturated solution, 48 h

sebacic acid (111-20-6)	
LC50 fish 1	> 100 mg/l Danio rerio 96 h; no mortality was observed
EC50 Daphnia 1	> 100 mg/l 48 h

succinimide (123-56-8)	
EC50 Daphnia 1	515 g/l 24 h

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

adipic acid (124-04-9)	
LC50 fish 1	>= 1000 mg/l 96 h
EC50 Daphnia 1	46 mg/l 48 h
Polyethylene Glycol (25322-68-3)	
LC50 fish 1	> 100 mg/l
LC50 other aquatic organisms 1	1000 mg/l
potassium sulfate (7778-80-5)	
LC50 fish 1	680 mg/l 96h Pimephales promelas
EC50 Daphnia 1	720 mg/l 48h
ErC50 (algae)	2700 mg/l Chlorella vulgaris
lithium sulphate (10377-48-7)	
LC50 fish 1	30.3 mg/l read-across, 96 h
EC50 Daphnia 1	33.2 mg/l read across, 48 h
LOEC (chronic)	24.35 mg/l read-across lithium hydroxide monohydrate
NOEC (chronic)	17.35 mg/l read-across lithium hydroxide monohydrate
calcium sulfate (7778-18-9)	
LC50 fish 1	> 56000 mg/l 96 h

12.2. Persistence and degradability

phenyl salicylate (118-55-8)	
Persistence and degradability	Moderately biodegradable.
2',4'-dimethylacetoacetanilide (97-36-9)	
Biodegradation	25 % 28 d
salicylamide (65-45-2)	
Biodegradation	99 % 28 d
sebacic acid (111-20-6)	
Persistence and degradability	Readily biodegradable.
succinimide (123-56-8)	
Persistence and degradability	Readily biodegradable.
Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.
adipic acid (124-04-9)	
Persistence and degradability	Readily biodegradable.
Biodegradation	90 % 5 d

12.3. Bioaccumulative potential

barium sulfate (7727-43-7)	
BCF fish 1	68.4 L/kg
phenyl salicylate (118-55-8)	
Log Pow	3.82
Bioaccumulative potential	Not established.
2',4'-dimethylacetoacetanilide (97-36-9)	
Log Pow	1.4

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

salicylamide (65-45-2)	
Log Pow	1.31
sebacic acid (111-20-6)	
Log Pow	1.5
succinimide (123-56-8)	
Log Pow	-0.9
adipic acid (124-04-9)	
BCF fish 1	3.162
Log Pow	0.093
potassium sulfate (7778-80-5)	
Bioaccumulative potential	This product is not bioaccumulating.
lithium sulphate (10377-48-7)	
Log Pow	-4.38

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

PBT: not yet assessed

vPvB: not yet assessed

Component	
potassium sulfate (7778-80-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code : For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not considered a dangerous good for transport regulations

14.2. UN proper shipping name

Proper Shipping Name (ADR) :

14.3. Transport hazard class(es)

Not applicable

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

14.4. Packing group

Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

No additional information available

14.6.2. Transport by sea

No additional information available

14.6.3. Inland waterway transport

Carriage prohibited (ADN) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

15.1.2. National regulations

Germany

Water hazard class (WGK) : 1 - low hazard to waters

WGK remark : Classification based on the R-phrases in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

according to Regulation (EU) No. 2015/830

Indication of changes:

Added. Product.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population

Tempilstik® 104 °F (40 °C), 131 °F (55 °C), 182 °F (83 °C), 200 °F (93 °C), 206 °F (97 °C), 213 °F (101 °C), 219 °F (104 °C), 225 °F (107 °C), 230 °F (110 °C), 239 °F (115 °C), 256 °F (124 °C), 263 °F (128 °C), 320 °F (160 °C), 325 °F (163 °C), 329 °F (165 °C), 374 °F (190 °C), 375 °F (191 °C), 383 °F (195 °C), 388 °F (198 °C), 392 °F (200 °C), 400 °F (204 °C), 413 °F (212 °C), 419 °F (215 °C), 550 °F (288 °C), 1400 °F (760 °C), 1450 °F (788 °C), 1500 °F (816 °C), 1550 °F (843 °C), 1600 °F (871 °C), 1650 °F (899 °C), 1700 °F (927 °C), 1800 °F (982 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 212 °F (100 °C), 257 °F (125 °C), 410 °F (210 °C), 554 °F (290 °C)

Safety Data Sheet

according to Regulation (EU) No. 2015/830

	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	TWA: Time Weight Average
	TSCA: Toxic Substances Control Act

Data sources

: ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.
 European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
 Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
 National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information

: None.

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Carc. 1A	Carcinogenicity (inhalation) Category 1A
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350i	May cause cancer by inhalation
H351	Suspected of causing cancer
H411	Toxic to aquatic life with long lasting effects
EUH210	Safety data sheet available on request

LA-CO EU CLP SDS

SDS Prepared by: The Redstone Group, LLC
 6077 Frantz Rd.
 Suite 206
 Dublin, OH USA 43016
 T 614-923-7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product